

# Agency Information

The certificate is only used for browsing on the web and proves that SETsafe | SETfuse has been certified.

If you need a FULL-VERSION certificate, please contact us: [sales@SETfuse.com](mailto:sales@SETfuse.com)

该证书只用于在网页浏览，证明SETsafe | SETfuse已获得认证，如需要完整版本证书，请联系我们: [sales@SETfuse.com](mailto:sales@SETfuse.com)

# JDYX8.E345932 - Fuses, Supplemental Certified for Canada - Component

## Fuses, Supplemental Certified for Canada - Component

XIAMEN SET ELECTRONICS CO LTD  
 8067 XIANG'AN XI RD XIAMEN TORCH  
 HIGH-TECH INDUSTRIAL DEVELOPMENT ZONE  
 XIANG'AN INDUSTRY DIST  
 XIAMEN, FUJIAN 361101 China

E345932

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
SCT520	5.2 x 20 (0.20 x 0.79)	0.4-10	250Vac	10000
		0.4-10	125Vac	10000
		0.4-10	300Vac	1500
		0.4-10	400Vac	300
		0.4-10	350Vac	300
		0.4-10	500Vac	200
		0.4-10	300Vdc	3000
		0.4-10	250Vdc	3000
		0.4-10	125Vdc	3000
		0.4-10	500Vdc	500
		0.4-10	450Vdc	500
		0.4-10	400Vdc	500
		0.4-10	350Vdc	500
		0.4-20	250Vac	1000
		0.4-20	125Vac	1000
		0.4-20	400Vac	300
		0.4-20	350Vac	300
		0.4-20	300Vdc	500
		0.4-20	250Vdc	500
		0.4-20	125Vdc	500
		0.4-30	300Vac	500
		0.4-30	250Vac	500
		0.4-30	125Vdc	500
Supplemental fuses: pigtail leads, filled-tube, cartridge enclosed				
SCT520P	5.2 x 20 (0.20 x 0.79)	0.4-10	250Vac	10000
		0.4-10	125Vac	10000
		0.4-10	300Vac	2000
		0.4-10	400Vac	300
		0.4-10	350Vac	300
		0.4-10	500Vac	200
		0.4-10	300Vdc	3000
		0.4-10	250Vdc	3000
		0.4-10	125Vdc	3000
		0.4-10	500Vdc	500
		0.4-10	450Vdc	500
		0.4-10	400Vdc	500
		0.4-10	350Vdc	500
		0.4-20	250Vac	1000
		0.4-20	125Vac	1000

		0.4-20	500Vac	300
		0.4-20	450Vac	300
		0.4-20	400Vac	300
		0.4-20	350Vac	300
		0.4-20	300Vdc	500
		0.4-20	250Vdc	500
		0.4-20	125Vdc	500
		0.4-30	250Vac	500
		0.4-30	250Vdc	500