

TVS Diodes

Transient Voltage Suppression Diodes

ASMC-VR Series




Description

Transient Voltage Suppressor (TVS) is a circuit protection component that either attenuates (reduces) or filters a transient voltage spike (overvoltage), TVS diodes provide critical protection by going into avalanche breakdown within no more than a few nanoseconds after a strike, clamping the transient voltage, and routing its current to the ground.

Applications

- Communication Equipment
- Security & Protection
- Industrial Control Equipment
- Power Supply
- Automotive Electronics
- New Energy
- Lightning Protection

Functional Diagram



Features


- AEC-Q101 Qualified
- Low incremental surge resistance
- Excellent clamping capability
- Low profile package with built-in strain relief
- Typical I_R less than 1.0 μA above 12 V
- 1500 W peak pulse power capability with a 10/1000 μs Waveform, repetition rate (duty cycle): 0.01%
- For surface mounted applications to optimize board space
- Typical failure mode is short from over-specified voltage or current
- IEC 61000-4-2 ESD 30 kV (Air), 30 kV (Contact)
- EFT protection of data lines in accordance with IEC 61000-4-4
- Very fast response time
- Glass passivated chip junction
- High temperature to reflow soldering guaranteed: 260 $^{\circ}C/30sec$
- $V_{BR} @ T_J = V_{BR}@25^{\circ}C \times (1 + \alpha T \times (T_J - 25))$
(αT : Temperature Coefficient, typical value is 0.1%)
- Plastic package is flammability rated V-0 per Underwriters Laboratories
- Meet MSL level1, per J-STD-020
- Matte tin lead-free plated
- Halogen free and RoHS compliant
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/JEDEC J-STD-609A.01)

TVS Diodes

Transient Voltage Suppression Diodes

ASMC-VR Series

Package Outline Dimensions (DO-214AB)



Mounting Pad Layout

Symbol	Millimeters		Inches	
	Min.	Max.	Min.	Max.
L	6.60	7.11	0.260	0.280
W	5.59	6.22	0.220	0.245
W ₁	2.90	3.20	0.114	0.126
H	2.06	2.62	0.079	0.103
T	0.152	0.305	0.006	0.012
L ₁	7.75	8.13	0.305	0.320
L ₂	0.76	1.52	0.030	0.060
D	-	0.203	-	0.008
A	-	4.20	-	0.165
B	2.40	-	0.094	-
C	2.40	-	0.094	-
E	3.30	-	0.129	-

Maximum Ratings and Characteristics

(Ratings at 25 °C ambient temperature unless otherwise specified.)

Parameter	Symbol	Value	Unit
Peak Pulse Power Dissipation(Fig.2) by 10/1000 us Test Waveform ⁽¹⁾⁽²⁾ (Fig.4) -Single Die Parts	P _{PPM}	1500	W
Peak Pulse Power Dissipation(Fig.2) by 10/1000 us Test Waveform ⁽¹⁾⁽²⁾ (Fig.4) - Stacked Die Parts ⁽⁵⁾	P _{PPM}	2000	W
Peak Power Dissipation on Infinite Heat Sink at T _L =50 °C	P _D	6.5	W
Peak Forward Surge Current,8.3 ms single half sinewave superimposed on rated load (JEDEC Method) ⁽³⁾	I _{FSM}	200	A
Maximum Instantaneous Forward Voltage at 100 A for Unidirectional Only ⁽⁴⁾	V _F	3.5/5.0	V
Operating Temperature Range	T _J	-65 to 150	°C
Storage Temperature Range	T _{STG}	-65 to 175	°C
Typical Thermal Resistance Junction to Lead	R _{θJL}	15	°C / W
Typical Thermal Resistance Junction to Ambient	R _{θJA}	75	°C / W

Notes


1. Non-repetitive current pulse, per Fig. 4 and derated above T_J(initial)=25 °C per Fig. 3.
2. Mounted on 8.0 mm² land areas.
3. Measured of 8.3 ms single half sine-wave or equivalent square wave, duty cycle=4 pulses per minute maximum.
4. V_F < 3.5 V for single die parts and V_F < 5.0 V for stacked-die parts.
5. For stacked die component details, please refer to part numbers labeled by * in Electrical Characteristics.

TVS Diodes



Transient Voltage Suppression Diodes

ASMC-VR Series

Part Numbering System



Marking



TVS Diodes

Transient Voltage Suppression Diodes

ASMC-VR Series

Electrical Characteristics ($T_A=25\text{ }^\circ\text{C}$ unless otherwise noted)Table 1

Part Number		Device Marking Code		Breakdown Voltage $V_{BR}@I_T$		Test Current I_T	Reverse Stand-off Voltage V_R	Max. Reverse Leakage $I_R@V_R$	Max. Peak Pulse Current I_{PPM}	Max. Clamping Voltage $V_C@I_{PPM}$
				Min	Max					
Uni	Bi	Uni	Bi	(V)		(mA)	(V)	(μ A)	(A)	(V)
ASMC5.0A-VR	ASMC5.0CA-VR	AGDE	ABDE	6.40	7.00	10	5.00	600.00	163.00	9.20
ASMC6.0A-VR	ASMC6.0CA-VR	AGDG	ABDG	6.67	7.37	10	6.00	500.00	145.70	10.30
ASMC6.5A-VR	ASMC6.5CA-VR	AGDK	ABDK	7.22	7.98	10	6.50	300.00	134.00	11.20
ASMC7.0A-VR	ASMC7.0CA-VR	AGDM	ABDM	7.78	8.60	10	7.00	200.00	125.00	12.00
ASMC7.5A-VR	ASMC7.5CA-VR	AGDP	ABDP	8.33	9.21	1	7.50	100.00	116.30	12.90
ASMC8.0A-VR	ASMC8.0CA-VR	AGDR	ABDR	8.89	9.83	1	8.00	50.00	110.30	13.60
ASMC8.5A-VR	ASMC8.5CA-VR	AGDT	ABDT	9.44	10.40	1	8.50	20.00	104.20	14.40
ASMC9.0A-VR	ASMC9.0CA-VR	AGDV	ABDV	10.00	11.10	1	9.00	10.00	97.40	15.40
ASMC10A-VR	ASMC10CA-VR	AGDX	ABDX	11.10	12.30	1	10.00	5.00	88.30	17.00
ASMC11A-VR	ASMC11CA-VR	AGDZ	ABDZ	12.20	13.50	1	11.00	1.00	82.50	18.20
ASMC12A-VR	ASMC12CA-VR	AGEE	ABEE	13.30	14.70	1	12.00	1.00	75.40	19.90
ASMC13A-VR	ASMC13CA-VR	AGEG	ABEG	14.40	15.90	1	13.00	1.00	69.80	21.50
ASMC14A-VR	ASMC14CA-VR	AGEK	ABEK	15.60	17.20	1	14.00	1.00	64.70	23.20
ASMC15A-VR	ASMC15CA-VR	AGEM	ABEM	16.70	18.50	1	15.00	1.00	61.50	24.40
ASMC16A-VR	ASMC16CA-VR	AGEP	ABEP	17.80	19.70	1	16.00	1.00	57.70	26.00
ASMC17A-VR	ASMC17CA-VR	AGER	ABER	18.90	20.90	1	17.00	1.00	54.40	27.60
ASMC18A-VR	ASMC18CA-VR	AGET	ABET	20.00	22.10	1	18.00	1.00	51.40	29.20
ASMC20A-VR	ASMC20CA-VR	AGEV	ABEV	22.20	24.50	1	20.00	1.00	46.30	32.40
ASMC22A-VR	ASMC22CA-VR	AGEX	ABEX	24.40	26.90	1	22.00	1.00	42.30	35.50
ASMC24A-VR	ASMC24CA-VR	AGEZ	ABEZ	26.70	29.50	1	24.00	1.00	38.60	38.90
ASMC26A-VR	ASMC26CA-VR	AGFE	ABFE	28.90	31.90	1	26.00	1.00	35.70	42.10
ASMC28A-VR	ASMC28CA-VR	AGFG	ABFG	31.10	34.40	1	28.00	1.00	33.10	45.40
ASMC30A-VR	ASMC30CA-VR	AGFK	ABFK	33.30	36.80	1	30.00	1.00	31.00	48.40
ASMC33A-VR	ASMC33CA-VR	AGFM	ABFM	36.70	40.60	1	33.00	1.00	28.20	53.30
ASMC36A-VR	ASMC36CA-VR	AGFP	ABFP	40.00	44.20	1	36.00	1.00	25.90	58.10
ASMC40A-VR	ASMC40CA-VR	AGFR	ABFR	44.40	49.10	1	40.00	1.00	23.30	64.50
ASMC43A-VR	ASMC43CA-VR	AGFT	ABFT	47.80	52.80	1	43.00	1.00	21.70	69.40
ASMC45A-VR	ASMC45CA-VR	AGFV	ABFV	50.00	55.30	1	45.00	1.00	20.60	72.70
ASMC48A-VR	ASMC48CA-VR	AGFX	ABFX	53.30	58.90	1	48.00	1.00	19.40	77.40

TVS Diodes

Transient Voltage Suppression Diodes

ASMC-VR Series

Part Number		Device Marking Code		Breakdown Voltage $V_{BR}@I_T$		Test Current I_T	Reverse Stand-off Voltage V_R	Max. Reverse Leakage $I_R@V_R$	Max. Peak Pulse Current I_{PPM}	Max. Clamping Voltage $V_C@I_{PPM}$
				Min	Max					
Uni	Bi	Uni	Bi	(V)		(mA)	(V)	(μ A)	(A)	(V)
ASMCJ51A-VR	ASMCJ51CA-VR	AGFZ	ABFZ	56.70	62.70	1	51.00	1.00	18.20	82.40
ASMCJ54A-VR	ASMCJ54CA-VR	AGGE	ABGE	60.00	66.30	1	54.00	1.00	17.30	87.10
ASMCJ58A-VR	ASMCJ58CA-VR	AGGG	ABGG	64.40	71.20	1	58.00	1.00	16.10	93.60
ASMCJ60A-VR	ASMCJ60CA-VR	AGGK	ABGK	66.70	73.70	1	60.00	1.00	15.50	96.80
ASMCJ64A-VR	ASMCJ64CA-VR	AGGM	ABGM	71.10	78.60	1	64.00	1.00	14.60	103.00
ASMCJ70A-VR	ASMCJ70CA-VR	AGGP	ABGP	77.80	86.00	1	70.00	1.00	13.30	113.00
ASMCJ75A-VR	ASMCJ75CA-VR	AGGR	ABGR	83.30	92.10	1	75.00	1.00	12.40	121.00
ASMCJ78A-VR	ASMCJ78CA-VR	AGGT	ABGT	86.70	95.80	1	78.00	1.00	11.90	126.00
ASMCJ85A-VR	ASMCJ85CA-VR	AGGV	ABGV	94.40	104.00	1	85.00	1.00	11.00	137.00
ASMCJ90A-VR	ASMCJ90CA-VR	AGGX	ABGX	100.00	111.00	1	90.00	1.00	10.30	146.00
ASMCJ100A-VR	ASMCJ100CA-VR	AGGZ	ABGZ	111.00	123.00	1	100.00	1.00	9.30	162.00
ASMCJ110A-VR	ASMCJ110CA-VR	AGHE	ABHE	122.00	135.00	1	110.00	1.00	8.50	177.00
ASMCJ120A-VR	ASMCJ120CA-VR	AGHG	ABHG	133.00	147.00	1	120.00	1.00	7.80	193.00
ASMCJ130A-VR	ASMCJ130CA-VR	AGHK	ABHK	144.00	159.00	1	130.00	1.00	7.20	209.00
ASMCJ150A-VR	ASMCJ150CA-VR	AGHM	ABHM	167.00	185.00	1	150.00	1.00	6.20	243.00
ASMCJ160A-VR	ASMCJ160CA-VR	AGHP	ABHP	178.00	197.00	1	160.00	1.00	5.80	259.00
ASMCJ170A-VR	ASMCJ170CA-VR	AGHR	ABHR	189.00	209.00	1	170.00	1.00	5.50	275.00
ASMCJ180A-VR	ASMCJ180CA-VR	AGHT	ABHT	201.00	222.00	1	180.00	1.00	5.10	292.00
ASMCJ200A-VR	ASMCJ200CA-VR	AGHV	ABHV	224.00	247.00	1	200.00	1.00	4.60	324.00
ASMCJ220A-VR	ASMCJ220CA-VR	AGHX	ABHX	246.00	272.00	1	220.00	1.00	4.20	356.00
ASMCJ250A-VR	ASMCJ250CA-VR	AGHZ	ABHZ	279.00	309.00	1	250.00	1.00	3.70	405.00
ASMCJ300A-VR*	ASMCJ300CA-VR*	AGJE	ABJE	335.00	371.00	1	300.00	1.00	3.10	486.00
ASMCJ350A-VR*	ASMCJ350CA-VR*	AGJG	ABJG	391.00	432.00	1	350.00	1.00	2.60	567.00
ASMCJ400A-VR*	ASMCJ400CA-VR*	AGJK	ABJK	447.00	494.00	1	400.00	1.00	2.30	648.00
ASMCJ440A-VR*	ASMCJ440CA-VR*	AGJM	ABJM	492.00	543.00	1	440.00	1.00	2.10	713.00

Notes:



- For bidirectional type having V_{BR} of 10 volts and less, the I_R should be doubled.
- For parts without A in the PN, the V_{BR} tolerance is $\pm 10\%$ and V_C is 5% higher than parts with A. The parts without A are currently available, but not recommended for new designs. The parts with A are preferred.
- For stacked die component details, please refer to models marked with * in electrical characteristics table.

TVS Diodes

Transient Voltage Suppression Diodes

ASMC-VR Series

I-V Curve Characteristics



Performance Curve for Reference ($T_A=25^\circ\text{C}$ unless otherwise noted)




FIGURE 1 TVS Transients Clamping Waveform




FIGURE 2 Peak Pulse Power Rating Curve




FIGURE 3 Peak Pulse Power Derating Curve




FIGURE 4 Pulse Waveform

TVS Diodes

Transient Voltage Suppression Diodes




FIGURE 5 Typical Junction Capacitance




FIGURE 6 Typical Transient Thermal Impedance




FIGURE 7 Maximum Non-Repetitive Forward Surge Current
Uni-Directional only




FIGURE 8 Peak Forward Drop vs Peak Forward Current
(Typical Values)


Environmental Specifications

High Temp. Storage	JESD22-A103
HTRB	JESD22-A108
MSL	JESDEC-J-STD-020, Level 1
Temperature Cycling	JESD22-A104
H3TRB	JESD22-A101
RSH	JESD22-A111

Physical Specifications

Weight	0.007 ounce, 0.21 grams
Case	JESD22DO214AB. Molded plastic body over glass passivated junction
Polarity	Color band denotes positive end (cathode) except Bidirectional
Terminal	Matte Tin-plated leads, Solderability per JESD22-B102

Soldering Parameters



Reflowing Condition

Reflow Soldering Parameters		Lead-Free Assembly
Pre-heat	Temperature Min ($T_{S (min)}$)	150 °C
	Temperature Max ($T_{S (max)}$)	200 °C
	Time (min to max) (t_s)	60 ~ 120 seconds
Average Ramp Up Rate (Liquidus Temp (T_L) to Peak)		3 °C / second max.
$T_{S (max)}$ to T_L Ramp-up Rate		3 °C / second max.
Reflow	Temperature (T_L) (Liquidus)	217 °C
	Time (min to max) (t_L)	60 ~ 150 seconds
Peak Temperature (T_P)		260 ^{+0/-5} °C
Time of within 5 °C of Actual Peak Temperature (t_p)		20 ~ 40 seconds
Ramp-down Rate		6 °C / second max.
Time from 25 °C to Peak Temperature		8 Minutes max.
Do Not Exceed		260 °C

TVS Diodes

Transient Voltage Suppression Diodes

ASMC-VR Series

Packaging Information

Tape	Symbol	Dimension (mm)
	W	16.00 + 0.30 / -0.10
	P ₀	4.00 ± 0.10
	P ₁	8.00 ± 0.10
	P ₂	2.00 ± 0.10
	D ₀	1.55 ± 0.05
	D ₁	1.55 ± 0.05
	E	1.75 ± 0.10
	F	7.50 ± 0.10
	A ₀	6.15 ± 0.10
	B ₀	8.30 ± 0.10
	K ₀	2.48 ± 0.10
	T	0.30 ± 0.05

Reel Size	13" Reel	
	A	330 mm
	C	13.2 mm
	W ₁	16.4 mm

Part Number	Package	QTY (Reel)	Packaging Option	Packaging Specification
ASMCxxx-VR	DO-214AB	3000 PCS	Tape & Reel – 16 mm tape/13" reel	EIA STD RS-481

Glossary

Item	Description
V_C	Clamping Voltage Voltage across TVS in a region of low differential resistance that serves to limit the voltage across the device terminals.
V_R	Reverse Stand-off Voltage Maximum voltage that can be applied to the TVS without operation. NOTE : It is also shown as V_{WM} (maximum working voltage (maximum d.c. voltage)) and known as rated stand-off voltage (V_{so}).
I_R	Reverse Leakage Current Current measured at V_R . NOTE : Also shown as I_D for stand-by current.
V_{BR}	Breakdown Voltage Voltage across TVS at a specified current I_T in the breakdown region.
I_{PPM}	Rated Random Recurring Peak Impulse Current Maximum-rated value of random recurring peak impulse current that may be applied to a device.
$P_{M(AV)}$	Rated Average Power Dissipation Maximum-rated value of power dissipation resulting from all sources, including transients and standby current, averaged over a short period of time.
P_{PPM}	Rated Random Recurring Peak Impulse Power Dissipation Maximum-rated value of the product of rated random recurring peak impulse current (I_{PPM}) multiplies by specified maximum clamping voltage (V_C).
C_J	Capacitance Capacitance across the TVS measured at a specified frequency and voltage.
V_{FS}	Peak Forward Surge Voltage Peak voltage across an TVS for a specified forward surge current (I_{FS}) and time duration. NOTE : Also shown as V_F .
I_{FS}	Forward Surge Current Pulsed current through TVS in the forward conducting region. NOTE : Also shown as I_F .
$\alpha_{V(BR)}$	Temperature Coefficient of Breakdown Voltage The change of breakdown voltage divided by the change of temperature.
I_{PP}	Peak pulse Current Peak pulse current value applied across the TVS to determine the clamping voltage V_C for a specified wave shape.
I_T	Pulsed D.C. Test Current Test current for measurement of the breakdown voltage V_{BR} . This is defined by the manufacturer and usually given in milliamperes with a pulse duration of less than 40 ms. NOTE : Also shown as I_{BR} .

—(GB-T 18802.321 / IEC 61643-321 / JESD210A)



ATTENTION

Usage

1. TVS must be operated in the specified ambient temp.
2. Do not clean the TVS with strong polar solvent such as ketone, esters, benzene and halogenated hydrocarbon, to avoid damaging the encapsulating layer.
3. Please do not apply severe vibration, shock or pressure to TVS, to avoid element cracking.

Replacement

1. If TVS is visually damaged, please replace it.
2. TVS is a non-repairable product. For safety sake, please use equivalent TVS for replacement.

Storage

1. Storage Temp. Range: (-55 to 150) °C.
2. Do not store the TVS at the high temp., high humidity or corrosive gas environment, to avoid influencing the solder-ability of the lead wires. The product shall be used up within 1 year after receiving the goods.

Environmental Conditions

1. TVS should not be exposed to the open air, nor direct sunshine.
2. TVS should avoid rain, water vapor or other condition of high temp. and high humidity.
3. TVS should avoid sand dust, salt mist, or other harmful gases.















Max. Typical Capacitance of TVS

The typical capacitance of TVS is listed in the specifications. Designers may refer to it when designing TVS in High frequency circuit.

Installation Mechanical Stress

1. Do not knock TVS when installing, to avoid mechanical damage.
2. Please do not apply severe vibration, shock or pressure to TVS, to avoid surface resin or element cracking.

Automotive TVS Diodes (Surface Mount) Feature Overview

Package Type	Series													
	DO-214AA	DO-214AB	DO-214AC	DO-218AB	ASMB	ASMB-VR	ASMC	ASMC-VR	ASMD	A5.0SMD	SM8SxxA	SM8SxxCA	SM8TxxA	SM8TxxCA
Product Outline (mm)														
V_R / V_{WM} (V) Reverse Stand-off Voltage	5.8 ~ 468	5.0 ~ 440	5.8 ~ 468	5.0 ~ 440	5.8 ~ 553	5.0 ~ 440	5.8 ~ 51	5.0 ~ 440	12.0 ~ 170	10.0 ~ 43.0	12.0 ~ 43.0	20.0 ~ 43.0	33.0 ~ 36.0	
P_{PPM} (W) (10/1000 μ s) Rated Peak Impulse Power Dissipation	400	600	400	600	1500	3000	5000	6600	8000					
Operating Temperature (°C)	-55 to +150								-55 to +175					